



JOHN DEERE

JOHN DEERE ROTARY TILLER

- + STRONG PTO ROTOR, LESS WARE AND TARE
- + STRONG SIDE DRIVE , SAVE MAINTENANCE COST
- + HEAVY DUTY GEAR
- + STRONG STRUCTURE WITH EQUIPMENT TO REDUCE VIBRATION
- + PAINTING WITH NANO TECHNOLOGY - LESS RUSTY
- + PTO GUARD FOR USER SAFETY

Model	3416RT	3419RT	3421RT
Tractor Compatability	3036E	5045D, 5050D	
3-Hitch Point	CAT I	CAT II	
Working Width, mm.	1650	1850	2050
Side Drive	Gear / Single Speed		
Gear Location	Off-Set	Center	
RPM Blade Rotor/PTO Rotor, rpm	215/540		
Number of Blade	48	54	60
Blade Type	C		
PTO	Safety Shear Bolt		
Working Depth, mm.	100-150		
Weight, kg.	305	334	366



PT WAHANA INTI SELARAS

Operational Office : Green Sedayu Bizpark, Blok GS 3/38,
 Jl. Cakung Cilincing Timur Raya KM 2, Jakarta 13910
 Phone : (+6221) 2983 2045, 2983 2113
 Email : admin.sales@wiselgroup.indomobil.co.id
 Website : wiselgroup.indomobil.co.id

Authorized Dealer for John Deere Asia Pte Limited
 Tractor - Farm Equipment