



Wheel Drive





er Sync Reverse



Narrow Track Width



Powerful Dual PTO



Metal Face Seals



Technical Specifications

ENGINE

Type 28HP, 2800 RPM, 3 Cylinder, Inline

FIP. Coolent cooled overflow reservoir, Naturally Aspirated

Air filter : Dry Type, Dual Element

TRANSMISSION

: Single Clutch

: 8 Forward + 8 Reverse. Gear box

FNR Synch Reverser

: Forward 1.6 to 20.7 Kmph Speeds

Reverse 1.7 - 21.5 Kmph

BRAKES

: Oil Immersed Disc Brakes Туре

HYDRAULICS

: 910 kgf Maximum Lift Capacity

STEERING

: Power Steering Type

POWER TAKE OFF

: Independent, 6 Splines Type : 540 @ 2492 ERPM Dual PTO

: 540 @ 1925 ERPM

WHEELS AND TIRES

: Front : 5 X 12 Rear: 8.3 X 24 Type

FUEL TANK

Capacity : 32 L

ELECTRICAL SYSTEM

: 55 Ah, 12V Battery, 50 Amp,

Alternator 12V. 12W Starter Motor

DIMENSION AND WEIGHT

: 1200 kg Total Weight

Turning Radius with Brakes : 2200 mm Turning Radius without Brakes : 2900 mm

FACTORY FITTED OPTIONS

Roll Over Protection System (ROPS) Seat and Seat Belt

FEATURES

- FNR NSS - Sync Reverser - Finger Guard

- Radiator Screen - Water Seperator - Digital hour meter

Underhood with downdraft exhaust muffler

Metal Face Seals

INDOMOBIL

Note: All options / features may not be available for single variant. Cardan Shaft Cover diameter more than 165 mm should not be used with 995mm setting (i.e with 5 X 12 & 8.3 X 24 tires)



Overall Width 995mm

High Lift Capacity

910

kqf

| Economical | Reliable | Easily available |



Clearance

Wheel Base 1574mm 285 mm

Overall Length 2520 mm

Overall

Height

2300 mm

For more information, please contact our authorized dealer:

John Deere Asia (Singapore) Private Limited 438 Alexandra Road #12-01/04 Alexandra Point, Singapore 119958



Operational Office: Green Sedayu Bizpark, Blok GS 3/38, Jl. Cakung Cilincing Timur Raya KM 2, Jakarta 13910, INDONESIA

: (+6221) 2983 2045, 2983 2113 : admin.sales@wiselgroup.indomobil.co.id Website: www.johndeere.indomobil.com

Authorized Dealer for John Deere Asia Pte Limited Tractor - Lamii Louisinen



Please note: Improvement in the product is a continuous process. Hence, the information given in this brochure is subject to change without prior notice. Accessories shown are not part of standard equipment.