





Spesification



ENGINE

Air filter

Type : John Deere 3029D, 55 HP,

2400 RPM, 3 cylinder Direct injection, Rotary F.I.P., Naturally Aspirated Coolant cooled with overflow reservoir

: Dry type, dual element

TRANSMISSION

Clutch : Dual

Gear Box : 9 Forward + 3 Reverse, Collarshift Speeds : Forward 2.05 to 28.8 kmph

Reverse 3.45 to 22.33 kmph

BRAKES

Self Adjusting, Self equalising,

Hydraulically Actuated, Oil immersed disk brakes

HYDRAULICS

Lifting capacity: 1800 kgf at lower link ends

3 Point linkage : Category II

Automatic depth & draft control

STEERING

Type: Power

STEERING COLUMN

Standard Model: Fixed type steering column **Premium Model**: Tiltable upto 25° with lock latch

POWER TAKE OFF

Type : Independent, 6 splines Standard Model RPM: 540 @ 2376 ERPM

Premium Model Dual PTC

Standard: 540 @ 2376 ERPM Economy: 540 @1705 ERPM

WHEELS AND TIERS

Front : 9.5 X 24 Rear : 16.9 X 28

FUEL TANK CAPACITY

: 68 lit

ELECTRICAL SYSTEM

100Ah, 12 volt, 40 Amp. alternator

2.5 KW starter motor

DIMENSIONS AND WEIGHT OF TRACTOR

Total weight : 2410 kg
Wheel base : 2060 mm
Overall length : 3580 mm
Overall width : 1875 mm
Ground clearance : 380 mm

ACCESSORIES

- Ballast Weight
- Canopy
- Canopy holder
- Wagon Hitch
- Drawbar

FEATURES	Standard	Premium
Multi Function Display		✓
Deluxe Seat With Arm Rest		✓
EQRL		✓
Single piece hood opening with gas struts	✓	√
Dual PTO		✓
Hand Rail & Exhaust Muffler Guard	✓	√
Finger guard	√	√
Tilt Steering		✓
Water Bottle holder	✓	✓
Side bar & Steps	✓	✓
Mobile Charger + Holder		✓
Go Home Feature		1



For more information, please contact our authorized dealer or nearest area office.



PT WAHANA INTI SELARAS

Operational Office : Green Sedayu Bizpark, Blok GS 3/38, Jl. Cakung Cilincing Timur Raya KM 2, Jakarta 13910, INDONESIA

Phone : (+6221) 2983 2045, 2983 2113

Email : admin.sales@wiselgroup.indomobil.co.id

Website : wiselgroup.indomobil.co.id

Authorized Dealer for John Deere Asia Pte Limited Tractor - Farm Equipment Please note: Improvement in the product is a continuous process. Hence the information given in this brochure is subject to change without prior notice.

Accessories shown are not the part of standard equipment.