

5075E

Tractor 75HP



JOHN DEERE

EXCELLENT TORQUE & FUEL EFFICIENT



Sugar Cane Application



Palm Oil Application


Accessories shown are not the part of standard equipment.

Technical Specification



ENGINE


| | |
|----------------------------------|--|
| Type | John Deere 75 HP, 2400 RPM, 3cylinders, Liquid cooled with over reservoir, Turbo charged |
| Max Torque (at 1700 engine rpm)* | 330 Nm |
| Displacement | 2,9 L |
| Fuel Tank Capacity | 68 L |
| Air Filter | Dry type, dual element |



GearPro™
Wider Speed Range

TRANSMISSION

| | |
|--------------|-----------------|
| Clutch Type | Dual Dry Clutch |
| Gearbox Type | 9x3 TSS |



PowerTech™
HPCR Engine

BREAKS

Hydraulically actuated, Oil immersed disk brakes

STEERING

| | |
|------|----------------|
| Type | Power Steering |
|------|----------------|

POWER TAKE OFF

| | |
|------|----------------------------------|
| Type | Independent PTO |
| RPM | 540 @1705 ERPM 540 @ 2376 RPM |

HYDRAULICS

| | |
|---------------------|-------------|
| Type | Open Center |
| Lift at Hitch balls | 2500 kgf |

WHEELS AND TIRES

| | |
|-------|-----------|
| Front | 12,4 x 24 |
| Rear | 18,4 x 30 |

WEIGHT AND DIMENSION

| | |
|------------------|--|
| Total Weight | 2475 kg |
| Wheel Base | 2050 mm |
| Overall Length | 3630 mm |
| Overall Width | 1901 mm |
| Overall Height | 2510 mm |
| Ground Clearance | 440 mm |
| Rear Wheel Width | Adjustable 5 levels 1366/1563/1665/1668/1770 |

*Incl. Max Torque Reserve



PT WAHANA INTI SELARAS

Operational Office : Green Sedayu Bizpark, Blok GS 3/38,
Jl. Cakung Cilincing Timur Raya KM 2, Jakarta 13910
Phone : (+6221) 2983 2045, 2983 2113
Email : admin.sales@wiselgroup.indomobil.co.id
Website : wiselgroup.indomobil.co.id

Authorized Dealer for John Deere Asia Pte Limited
Tractor - Farm Equipment



Please note: Improvement in the product is a continuous process.
Hence the information given in this brochure is subject to change without prior notice.