

5E Series

John Deere Tractors (77 - 89 hp)



JOHN DEERE



5E Series

John Deere Tractors (77 - 89 hp)



JOHN DEERE

Engine	5076E	5082E	5090E
Engine horsepower at rated engine speed	77 hp (57.4 kW)	81 hp (60.4 kW)	89 hp (66.4 kW)
Rated engine speed	2400 rpm		
Maximum torque	292 Nm 1220 rpm	292 Nm 1220 rpm	318 Nm 1600 rpm
Cylinders	4		
Aspiration	Natural	Natural	Turbo
Option	Turbo	Turbo	NA
Capacity	4.5 L (276 in ³)		
Compression	17.6:1	17.6:1	17.0:1
Injection pump	Rotary		

Transmission			
Standard	Synchronized		
Gears	9 forward / 3 reverse		
Optional	N/A	PowrReverser™	
Gears	N/A	12 forward / 12 reverse	
Inversor	N/A	Yes, electro-hydraulic	

Clutch			
Type	Dry		
Option	N/A	Wet with PowrReverser™	
Material	Cerametallic		
Bore	279 mm (11 in ³)		

Power Take-Off			
PTO horsepower	66 hp	70 hp	77 hp
Control	Independent		
Speed	540 rpm		
Option	N/A	540E Economic with PowrReverser™	
Activation	Mechanical		
Activation	N/A	Electro-hydraulic with PowrReverser™	

Hydraulic system			
Type	Open center		
Pump type	Gears		
Implement pump capacity	60.2 L/min		
Max pressure at implement	19 MPa / 2755 lb/in ²		
Hitch lift capacity	1530 kg		
System sensibility	3 point		
Hitch category	1 and II		
Selective control valve	1 (2 nd optional)		

Steering			
Type	Hydrostatic		
Steering flow	24.9 L/min		

Rear Axle			
Differential lock	Mechanical by pedal		
Brakes type	Wet multi-disk self-adj		
Activation	Hydraulic		

Electric system			
Alternator	70 A	70 A / 90 A (Cab)	
Starter motor	3.39 hp (2.5 kW)		

Capacities			
Fuel Tank	95 L	95 L / 125 L with cab	
Cooling system	10.8 L		
Engine oil	8.5 L		
Transmission oil, differential and hydraulic system	38 L		

Dimensions	5076E	5082E	5090E
Wheelbase	2127 mm	2180 mm	
Overall length	3295 mm		
Overall width, rear axle	2100 mm		
Height to top of ROPS	2495 mm	2540	
Height to steering wheel MFWD	1740 mm	1970 mm	
Minimum clearance to ground MFWD	320 mm	420 mm	
Approximate shipping weight MFWD	2500 kg 2WD / 2600 MFWD		

Tires			
Front standard	10.0 - 16 2WD / 13.2 - 24 MFWD		
Front optional MFWD	11.2 - 24 / 12.4 - 24		
Rear standard	15.5 - 38		
Rear optional	16.9 - 30 / 18.4 - 30		

Rear tires 16.9 x 30 R1 (km/h) for all 5E Series models

Speeds			
Forward at 2400 rpm			
A1 2.1 km/h			C1 11.3 Km/h
A2 3.1 km/h			C2 19.9 km/h
A3 4.2 km/h			C3 27.1 Km/h
B1 5.0 km/h			R1 3.6 km/h
B2 7.2 km/h			R2 8.4 km/h
B3 9.9 km/h			R3 23.2 km/h

Basic equipment		
- Water tramp in fuel system	- Fuel pre-filter	- Foldable steering column (except 5076E)
- Double element air filter	- Drawbar with fork connector	- SMV Emblem
- Operator seat with seatbelt	- Roll over protection	- Foot throttle
- Front weight support	- Front weight support	- 3 working lamps (2 front and 1 rear)
		- 7 pin connector
		- 1 st selective control valve
		- Operators manual

Optional Equipment		
- Front counterweights	- Front fenders (MFWD)	- Standard and Deluxe canopy
- Rear counterweight	- Tool box	- Creeper (speed reductor)
		- 2 nd selective control Valve
		- Double medium valve with Joystick

Cab Standard Equipment		
- Isolated cab	- Air conditioner and heater	- Preparation for AM/FM radio
- Fabric seat with mechanical suspension	- Safety belt	- 2 speakers
- Folding steering column	- Front windshield with wiper	- Preparation for Greenstar™ system with PowrReverser™ transmission
- Interior rearview mirror	- Interior light, front and rear warning lights	- 12V connector lighter type
		- 12V connector with 3 pins
		- 4 working lamps (2 front and 2 rear)
		- Cup holder



PT WAHANA INTI SELARAS
 Operational Office : Green Sedayu Bizpark, Blok GS 3/38,
 Jl. Cakung Cilincing Timur Raya KM2, Jakarta 13910, INDONESIA
 Phone : (+6221) 2983 2045, 2983 2113
 Email : admin.sales@wiselgroup.indomobil.co.id
 Website : www.johndeere.indomobil.com

Authorized Dealer for John Deere Asia Pte Limited
 Tractor - Farm Equipment

This literature has been compiled for worldwide circulation. While general information, pictures, and descriptions are provided, some illustrations and text may include finance, insurance, product options and accessories NOT AVAILABLE in all regions. PLEASE CONTACT YOUR LOCAL DEALER FOR DETAILS. John Deere reserves the right to change specification, design and price of products described in this literature without notice. John Deere, the leaping deer symbol, and John Deere's green and yellow trade dress are the trademarks of Deere & Company.